

Williams 4x4










CUSTOM BUILT WINCH BARS

0800 4711NZ

WF170 – 12v 17000lb 4WD Winch



Accessories included

	Mounting plate WFMO		Pulley block WFPB170		Lanyard WFLA		Handlebar switch N/A		Fairlead WFFL	
Hook WHO170		Cables WFBC17		Control Box WFS01217		Lanyard plug lead N/A		Remote REMO		Pull strap WRPS

Performance / Specifications

Single line rated pull	17000lb/7727kg	Gear Reduction ratio	358:1
Motor	Series Wound, 12v DC, 6hp	Cable	12mm x 26m
Overall Dimensions (mm)	555L x 196W x 249H	Weight	53.5kg

Line Speed and Current Drain (first layer)

Line Pull lb/kg	0	2000lb/ 909kg	4000lb/ 1818kg	6000lb/ 2727kg	8000lb/ 3636kg	10000lb/ 4545kg	12000kg/ 5682kg	15000lb/ 6818kg	17000lb/ 7727kg
Line Speed (mpm)	7.28	3.7	2.8	2.25	1.83	1.55	1.34	0.95	0.9
Current Drain	68	100	155	185	235	275	330	455	520

Line Pull Capacity – Based on first layer on drum

Cable Layer	1	2	3	4
Rated Line Pull per Layer	17000lb/7727kg	15482lb/7037kg	12584lb/5720kg	10550lb/4795kg
Total rope on drum	6.22m	12.94m	20.35m	26m

ON ROAD – OFF ROAD – ANY ROAD